

DECLARATION OF PERFORMANCE NO. 5/2017

1. Unique identification code of the product:	ACKERMAN K3	
2. Intended use/es:	Solid fuel heater intended for heating residential premises	
3. Name and contact address of the manufacturer:	ACKERMAN S.A. ul. Lektykarska 54, 01-687 Warszawa, Poland	
4. Name and contact address of the authorised representative:	Not applicable	
5. System or systems of assessment and verification of constancy of performance of the product:	System 3	
6. Harmonised standard:	EN 13240:2001/A2:2004/AC:2007	
7. Name and identification number of the notified body and the number of the test report:	Instytut Nafty i Gazu – Państwowy Instytut Badawczy, notified body no. 1450 performed the verification of performance of the product and issued test report no. 3209 A4 16	
8. DECLARED PERFORMANCE		
Essential characteristics:	Performance:	Harmonised technical specification:
Fire safety:		EN 13240:2001/A2:2004/AC:2007
- Safety distances to combustible materials	Minimal distance in mm: Floor under the appliance = 0 Front, back, side, top = 1500 Floor under the appliance should be made of non-combustible materials	EN 13240:2001/A2:2004/AC:2007
- Hazards related to the loss of the firebed and escape of harmful combustion gases into the room	No hazards	EN 13240:2001/A2:2004/AC:2007
- Safety of fuel filling	Pass	EN 13240:2001/A2:2004/AC:2007
- Equipping the device with an adjustable and properly marked adjustment device	Pass	EN 13240:2001/A2:2004/AC:2007
- Keeping heating surfaces clean	Pass	EN 13240:2001/A2:2004/AC:2007
- Proper and efficient appliance operation	Pass	EN 13240:2001/A2:2004/AC:2007
Electrical safety	Not applicable	EN 13240:2001/A2:2004/AC:2007
Nominal heat output	7,2 kW	EN 13240:2001/A2:2004/AC:2007
Heating efficiency	78,7%	EN 13240:2001/A2:2004/AC:2007
CO emission in combustion products at 13% O ₂	0,14%	EN 13240:2001/A2:2004/AC:2007
Refuelling intervals	0,75 h	EN 13240:2001/A2:2004/AC:2007
Flue gas temperature at nominal heating power	320°C	EN 13240:2001/A2:2004/AC:2007
Temperature rise of the operating components	Operating components: 75 K ÷ 141 K Manufacturer supplies safety operating tool with the appliance	EN 13240:2001/A2:2004/AC:2007
Surface temperature	Pass	EN 13240:2001/A2:2004/AC:2007
Durability	Pass	EN 13240:2001/A2:2004/AC:2007
Mechanical resistance (to carry a chimney/flue)	Pass	EN 13240:2001/A2:2004/AC:2007
Release of dangerous substances	No release of dangerous substances	EN 13240:2001/A2:2004/AC:2007

The performance of the product identified above is in conformity with the set of declared performance/s.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Warsaw, June 2nd, 2017
Dariusz Matulka, CEO



ACKERMAN SA
01-687 Warszawa, ul. Lektykarska 54
tel. 22 490 99 00, fax: 22 490 99 01
NIP: 701-02-19-301, REGON: 142193055
KRS: 0000531766